

M8

0810 0800 ... 0...

## Cordsets M8



Actuator/sensor cordset with overmolded connectors

**Cable end 1:**

M8 male, straight, A-coded, IP67

**Cable end 2:**

M8 female, straight, A-coded, IP67

**Cable:**


PVC, black

---


Approvals:



**M8** 0810 0800 ... 0...



Pin assignment for female M8 connectors, A-coded, front view



**Environmental conditions**

Temperature range -25 °C/+80 °C

**Materials**

Insulating body	TPU GF, HB according to UL94
Contact bush	CuZn, pre-nickel and gold-plated
Contact pin	CuZn, pre-nickel and gold-plated
Overmolding/handle	PVC <sup>1</sup>
Knurled screw	CuZn, nickel-plated
Knurled nut	CuZn, nickel-plated
Seal	FKM

<sup>1</sup> gemessen mit einem passenden Gegenstück

**Mechanical data**

Mating cycles	≥ 100
Insertion force	≤ 23 N <sup>1</sup>
Withdrawal force	≤ 23 N <sup>1</sup>
Protection class	IP67 <sup>2</sup>

<sup>1</sup> gemessen mit einem passenden Gegenstück

<sup>2</sup> according to IEC DIN EN 60529, only in locked condition with an appropriate counterpart

**Connected cable**

Outer jacket PVC, black


**Electrical data (at T<sub>amb</sub> 20 °C)**

Contact resistance	≤ 10 mΩ
Rated current	4 A (3-4 poles) 1.5 A (6-8 poles) (T <sub>amb</sub> 40 °C)
Rated voltage	50 V AC/60 V DC (3-4 poles) 32 V AC/DC (6-8 poles) (with pollution degree 3)
Rated impulse voltage	1.5 kV (3-4 poles) 0.8 kV (6-8 poles)
Material group	I (IEC)/0 (UL) (CTI = 600)
Overvoltage category	III
Insulation resistance	> 100 MΩ


M8

0810 0800 ... 0...


Pin assignment of male M8 connectors, front view




3 pole  
1 brown  
3 blue  
4 black



4 pole  
1 brown  
2 white  
3 blue  
4 black



6 pole  
1 brown  
2 white  
3 blue  
4 black  
5 gray  
6 pink



8 pole  
1 white  
2 brown  
3 green  
4 yellow  
5 gray  
6 pink  
7 blue  
8 red

Associated products

Counterparts

<a href="#">0800 ... 0...</a>	<a href="#">0800 ... 3...</a>	<a href="#">0800F1 ... 0...</a>
<a href="#">0800F1 ... 3...</a>	<a href="#">0805 ... 0...</a>	<a href="#">0805F1 ... 0...</a>
<a href="#">0806 ... L1 0...</a>	<a href="#">0806 ... L1 3...</a>	<a href="#">0820 ... T8CW ...</a>
<a href="#">0821 ... T10CP</a>	<a href="#">0822 ...S9 T8CP</a>	<a href="#">1210 0800 ... 3...</a>
<a href="#">1210 0806 ... L1 3...</a>	<a href="#">5000 04L1 3...</a>	<a href="#">5000 08L1 3...</a>
<a href="#">5000 10L1 3...</a>	<a href="#">5000 12L1 3...</a>	<a href="#">5012 04L1</a>
<a href="#">5012 08L1</a>	<a href="#">5012 10L1</a>	<a href="#">6157 8055 S01 4W</a>
<a href="#">6157 8055 S03 8W</a>	<a href="#">6157 8055 S06 16W</a>	<a href="#">6157 8055 S09 24W</a>

Accessories

<a href="#">9908 CPF0</a>	<a href="#">9908 CPM0</a>
---------------------------	---------------------------

M8

0810 0800 ... 0...

Designation	Pole Number	Connected Cable	PU (Pieces)	MDQ (Pieces)	Dimensions L (mm)
0810 0800 03 001 0,6m	3	PVC, black, 3 x 0.34 mm <sup>2</sup> (AWG 22), 910001, UL-style 2464	5	10	600
0810 0800 03 001 1,5m	3	PVC, black, 3 x 0.34 mm <sup>2</sup> (AWG 22), 910001, UL-style 2464	5	10	1500
0810 0800 03 001 2m	3	PVC, black, 3 x 0.34 mm <sup>2</sup> (AWG 22), 910001, UL-style 2464	5	10	2000
0810 0800 04 002 6m	4	PVC, black, 4 x 0.34 mm <sup>2</sup> (AWG 22), 910002, UL-style 2464	1	10	6000
0810 0800 06 024 0,6m	6	PVC, black, 6 x 0.25 mm <sup>2</sup> (AWG 24), 910024, UL-style 2464	5	10	600
0810 0800 06 024 2m	6	PVC, black, 6 x 0.25 mm <sup>2</sup> (AWG 24), 910024, UL-style 2464	5	10	2000
0810 0800 08 025 0,6m	8	PVC, black, 8 x 0.14 mm <sup>2</sup> (AWG 26), 910025, UL-style 2464	5	10	600
0810 0800 08 025 2m	8	PVC, black, 8 x 0.14 mm <sup>2</sup> (AWG 26), 910025, UL-style 2464	5	10	2000

**Packaging:**  
in a plastic bag